



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE METAL WORKING FLUID

LUBRIPLATE Metal Working Fluid is a specially developed product suitable for a variety of metal working applications. The 12-ounce aerosol can, including extension spout, makes it the ideal lubricant for:

Drilling
Sawing
Tapping
Grinding
Thread Chasing
Pipe Cutting
Filing
Nut Busting And Much More !!!

DOES NOT CONTAIN FLUOROCARBONS - DOES NOT CONTAIN 1,1,1 TRICHLOROETHANE

Typical Tests

Viscosity SUS @ 100°F	150
cSt @ 40°C	32
Viscosity SUS @ 210°F	45
cSt @ 100°C	6
ISO Grade	32
SAE Grade	10
Flash Point °F/°C	310/154
Fire Point °F/°C	350/177
Pour Point °F/°C	-40/-40
Specific Gravity	0.906
Color	L-3

Packaging Available

Carton, 12/12 oz. aerosol cans

Part No.

L0185-063